

# Updating Configuration Settings

In addition to the default network configuration information gathered from the initial configuration of the CSN, the **Configuration** tab of the **Content Storage** object allows for the editing of several additional configuration parameters. Any changes to these settings will not take effect until the cluster is rebooted to pick up the new configuration. The following options are available on the **Configuration** tab:

- **Cluster Name:** The read-only name of the cluster that was specified during the initial network configuration process.
- **Cluster Settings UUID:** Use this field to enter the UUID displayed in the settings popup of the Netmail admin console the first time a settings change is made. This will ensure the settings will persist across reboots.
- **Minimum Replicas:** The minimum number of stream instances that must be kept in the cluster. The value must be 1 or higher. A value of 2 is recommended and is provided as the default value.
- **Maximum Replicas:** The maximum number of stream instances that can be specified in the cluster. The value must be 1 or higher and must equal or exceed the value of minimum replicas.

The screenshot displays the Netmail Administration Console interface. The top header shows the 'netmail' logo on the left and 'Log Out admin.devorg01.ca' on the right. A navigation sidebar on the left lists various components: netmail Platform, Secure, Archive, Store, Cluster Services, Content Storage (highlighted), Content Router, and Index Server. The main content area is titled 'Configuration' and includes sub-tabs for 'Configuration', 'Licensing', and 'User Access'. The 'Configuration' sub-tab is active, showing 'Object Storage Configuration Settings'. Below this, instructions state: 'Enter storage configuration and click 'Update'. \* Indicates required fields.' The configuration fields are: 'Cluster Name' (read-only, value: castor.madev.com), 'Cluster Settings UUID' (empty text input), 'Minimum Replicas' (required, value: 3), and 'Maximum Replicas' (required, value: 4). At the bottom of the configuration area are three buttons: 'Update', 'Cancel', and 'View Storage Console'. The footer of the console reads 'Messaging Architects.'

Please refer to [Appendix A - Node Configuration](#) for more details on all Netmail Store configuration options. The Netmail Administration Console should be used for all configuration updates, but, for reference purposes, all cluster-wide configuration parameters set for Netmail Store are stored in a single configuration file (`/var/opt/caringo/netboot/cluster.cfg`). This file is automatically generated and should never be manually edited unless under direction of Support.

The **Configuration** tab also contains a **View Storage Console** button that allows you to view cluster status information such as number of nodes, cluster status, number of errors, number of streams, and capacity data. Refer to the [Viewing the Storage Console](#) page for more information about the Storage Console.