

Configuring the SCSP Proxy

The SCSP Proxy tab allows you to change the proxy log level, as well as modify or add a cluster. The SCSP Proxy installation on the CSN allows for clients on the external network, including remote clusters using Content Router, to send and receive SCSP requests to and from Netmail Store nodes on the internal network. The SCSP Proxy is configured during the network bootstrap process to listen on port 80 of both the external and internal interfaces. The log level for the Proxy can be changed from the user interface by selecting an alternate value from the dropdown and clicking **Update**.

The SCSP Proxy is also capable of communicating with remote clusters to perform operations like global infos for one or more objects. To add a remote cluster to the configured list, click the **Add Cluster** button. To edit an existing remote cluster, click the **Edit** button. To delete a cluster from the list, click the checkbox in the Delete column next to the cluster that should be deleted and then click **Update**.

The screenshot shows the Netmail Administration Console interface. The top navigation bar includes tabs for Configuration, SNMP Access, Netboot Management, User Access, Backup and Restore, and SCSP Proxy. The SCSP Proxy tab is active. The main content area is titled "SCSP Proxy" and contains "Cluster Services SCSP Proxy Settings". Below this, there are instructions: "Instructions: Change proxy log level and click 'Update and Restart', this will automatically restart the proxy." A "Log Level" dropdown menu is set to "10: Debug". Below that is a table for "Remote Cluster Name" with columns for "Host", "Port", "User ID", and "Delete". The table contains one entry: "madev" with Host "10.10.4.9", Port "80", and User ID "admin". There is a checkbox in the "Delete" column and an "Edit" button. Below the table are buttons for "Add Cluster", "Update and Restart", and "Cancel".

The following information is required for all configured remote clusters:

Parameter	Description
Remote Cluster Name	The alpha-numeric name for a remote cluster that will be used in requests sent to the proxy. May not contain whitespace. May be the DNS name for the cluster but that is not required.
Host	The IP address or hostname of the remote proxy the local proxy will communicate with. May not contain whitespace.
Port	The port on which the remote proxy will listen incoming requests. This is usually port 80. May not contain preceding or trailing whitespace.
User ID	The name of an administrator that belongs to the Netmail Store Administrators group for the remote cluster. May not contain whitespace.
Password/Confirm Password	The password for the administrator specified in the User ID field. This value may contain spaces as long as they are not leading or trailing.

The Netmail Administration Console should be used for all configuration updates, but, for reference purposes, all SCSP Proxy configuration parameters are stored in the `/etc/caringo/scspproxy/scspproxy.cfg` and `/etc/caringo/scspproxy/hosts.cfg` configuration files. These files are automatically generated and should never be manually edited unless under direction of your support personnel.

The `scspproxy` service will be started automatically after the initial configuration of the CSN. If needed, it can be started, stopped or restarted via a standard `init.d` script:

```
/etc/init.d/scspproxy {start|stop|status|restart}
```